


# TEC1H-30-30-44/80

## industrial high power peltier element




### thermal and electrical data:

thermal force:

resistance:

thermal conductivity:

$\alpha_{300K}$	0.0538	$\frac{V}{K}$
$\rho_{300K}$	3.41	$\Omega$
$\gamma_{300K}$	0.313	$\frac{W}{K}$



available maximum operating temperatures:  $T_{max}$  80, 120, 150(non-ROHS!), 200 °C  
 typical tolerances:  $\pm 5\%$

### mechanical data:

size of cold side:

$$L \times B \times H \quad 30.0 \times 30.0 \times 3.60 \text{ mm}$$

size of hot side:

$$L_{hot} \times B_{hot} \quad 30.0 \times 30.0 \text{ mm}$$

height tolerance:

$$\Delta H \quad \pm 0.25 \text{ mm}$$

length and width tolerances:

$$\Delta L \text{ and } \Delta B \quad +0.5 / -0.2 \text{ mm}$$

weight:

$$m \quad 15 \text{ g}$$

ceramic plates:

BK-100 (grey), BK-96 (white) or AlN (opaque)

location of production:

Russia

### experimental data:

typical values at:

		$T_h = 50^\circ C:$	$T_h = 300 K:$
maximum cooling power:	$Q_{max}$	44.3 W	38.2 W
	at $\Delta T = 0$ and $I_{Q_{max}}$	5.1 A	4.7 A
maximum temperature difference:	$\Delta T_{max}$	80.0 K	71.0 K
	at $Q = 0$ and $I_{\Delta T_{max}}$	3.8 A	3.6 A
	$U_{max}$	17.4 V	16.1 V

### order information:

TEC1H-30-30-44/80-B: max. 80°C  
 TEC1H-30-30-44/80-C: max. 120°C  
 TEC1H-30-30-44/80-D: max. 150°C  
 TEC1H-30-30-44/80-G: max. 200°C

TEC1H-30-30-44/80-BS: sealed, max. 80°C  
 TEC1H-30-30-44/80-CS: sealed, max. 120°C  
 TEC1H-30-30-44/80-DS: sealed, max. 150°C  
 TEC1H-30-30-44/80-GS: sealed, max. 200°C