



	1"	2/3"	1/1.8"
FOCAL LENGTH	f=16mm		
F-NUMBER	F=1:1.4,2.8,4,8		
PICTURE SIZE	9.6x12.8mm	6.6x8.8mm	5.4x7.2mm
ANGLE OF VIEW (∞)	VER. ANGLE	33.6°	23.2°
	HOR. ANGLE	44.3°	30.8°
	DIA. ANGLE	54.3°	38.3°
DISTORTION (TV)	-1.0%	-0.7%	-0.4%
FIELD OF VIEW (MINIMUM FOCUS DISTANCE)	VER.	186.2mm	126.8mm
	HOR.	251.5mm	170.3mm
	DIA.	318.3mm	214.6mm
MINIMUM FOCUS DISTANCE	0.3m		
FLANGE BACK	17.526mm in air		
BACK FOCUS	12.6mm in air		
FILTER SCREW SIZE	M35.5x0.5		
FRONT/REAR EFFECTIVE DIA.	FRONT φ21.5mm		REAR φ18.8mm
MOUNT	C-MOUNT		
EXIT PUPIL	-128.5mm		
TEMPERATURE RANGE	-10~+50°C		
STORAGE TEMPERATURE RANGE	-20~+60°C		
RESOLUTION CENTER/CORNER	CENTER 100lp/mm		CORNER 80lp/mm
WEIGHT	120g		

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



		尺度	1/1	工場番号	HR977SR
		機種名	F1.4/f16mm耐振レンズ		
2018.4.27	フォーカス環寸法変更 (Lock Ringをマウント側へ1mm移動)	機種番	LM16HC-V		
2016.2.8	最近接時長さ修正 53.85→54.25 重量記載				
2015.9.8	作成年月日				