
	REVISION	S	
REV.	DESCRIPTION	DATE DONE DONE BY CHECKED BY	3.0
0	INITIAL RELEASE	17.DEC.18 CHRIS	3.0 → 2X M3×0.5 × ▼4.0
			53.0
		29.0 0.0 0.0 0.0	USB3 CONNECTOR STATUS LED GPIO CONNECTOR  JACKSCREW BOSS
		2X M3x0.5	× ¥4.0
	BARREL LENGTH - "A" (+0.10/-0.15)		
SE	NSOR C-MOUNT CS-MOUNT		
	X421 6.5 -		23.0 8 23.0
IM	X422 6.5 –		
	X425 6.5 –		<u> </u>
	X428 6.5 –		
	X429 6.5 -		30 - 330 - 00
	X430 6.5 –		3.0 33.0
IM	X432   6.5   -	DDADDIETADY AND CONFIDENTIAL 7DD	ANGLE DOOL LINESCO STUEDWISE SCALEDWO NO CHEET DEV



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS
THE SOLE PROPERTY OF FLIR INTEGRATED IMAGING
SOLUTIONS. ANY REPRODUCTION IN PART OR
WHOLE WITHOUT THE WRITTEN PERMISSION OF FLIR
INTEGRATED IMAGING SOLUTIONS IS PROHIBITED.



UNLESS OTHERWISE	SCALE	DWG N	0
STATED:	1.1	BFS	_

LESS OTHERWISE	3
STATED:	

STATED:	1:1	BFS-XL-02-R0
ALL DIMENSIONS IN MM		TITLE
MACHINE FINISH 1.6µM	Α	BFS-XL USB

SHE	ΞΤ		RE
1	OF	3	(

A BFS-XL USB