


REV.	DATE	DESCRIPTION	BY
1.0	Aug/02/11'	D2503	Catherine
1.1	Dec/19/12'	R-2201	Eve

DATE :	Aug/02/11'
P/N :	B0106202
Dwg No:	A06491
CUST. P/N :	USB3C-A/1-CS/1-A-0
CUSTOMER :	
DESCRIPTION	USB3C-A/1-CS/1-A-0
APPROVE:	

CONFIGURATION



SPECIFICATION OF MATERIAL

1. END A

CONT. PLATING	Gold 30u"	MOLD No.	CMS-USB40	SHIELD'G	-
CONNECTOR TYPE	USB-9MASS30NBU	T. SCREW	-		


2. END B

CONT. PLATING	Gold 30u"	MOLD No.	CMS-USB41	SHIELD'G	-
CONNECTOR TYPE	USB-10MDSS30NB	T. SCREW	Jack Screw M2 Size :4.00x33.00x7.00		

3. WIRES

WIRE GAUGE	28Awg&28Awg&24Awg	LENGTH	1000+20-0mm	SHIELD'G	AB
CONDUCTORS	(1TP+MAE)x2+(1TP+AL)+2C	COLOR	Blue (301U)	UL/CSA	UL2725 (USB3.0)
JACKET MAT'L	PVC	INS. MAT'L	FM-SKIN-PE&FM-PE&SR-PVC	WIRE O.D.	5.5mm

4. CONNECTOR PIN OUT



5. SPECIAL REQUIREMENTS

- 5.1 Product requirement for Green environment protection:RoHS.
- 5.2 Overmold PVC is 45P Blue (Pantone No.:301U)(RoHS).

* Standard Product

ELII USB 3.0 Active Cable (OD6.0)


Published December 2013
Ver. 1.0

Approved :	Project No.	Rev. No.	Page
	UL style: UL2725	Draft	2

Product Specification – ELII USB 3.0 Active Cable (OD6.0)

Eye Pattern Testing Schematic Diagram


**Input Signal Source: Swing Voltage 800mV; EQ(Equalizer)=0, DE(De-emphasis)= 0




Eye Pattern

1M Passive cable

TX



RX




ELII USB 3.0 Active Cable (OD6.0)

Published December 2013
Ver. 1.0


Eye Pattern

5M Active cable

TX




RX




10M Active cable

TX




RX



REV	ECN	DESCRIPTION	DATE	DRAWN	APPROVED
1		Initial Release	03-22-13	jld	FLiburdi

CUSTOMER COPY



CONNECTOR PIN OUT




Table:

ITEM	DESCRIPTION	MATERIAL	P/N
D	MICRO USB B PLUG CONNECTOR	SPEC.	MICRO USB B TYPE
C	USB3.0 CABLE	SEE NOTES 2	-----
B	OVERMOLD	60P PVC/BLUE 301U	-----
A	STD A PLUG CONNECTOR	SPEC.	USB-9MASSXXXX

NOTES:

- 1.SPECIFICATIONS:
VOLTAGE: 30 VAC(RMS)
CURRENT: 1AMP MAX./CONTACT
TERMINATION RESISTANCE: 30MILLIOHMS MAX.
INSULATION RESISTANCE: 1000MEGOHMS MIN.
DIELEC.WITHSTANDING VOLTAGE: 750VAC
CAPACITANCE: 2pF MAX.
IMPEDANCE: 90 ±7 OHMS
TEMP.RANGE: -40°C TO 60°C STORAGE
HUMIDITY: 90 TO 95%RH
THERMAL SHOCK: -55°C TO +85°C
- 2.CABLE SPEC.:
UL20276,24AWG(2C),28AWG(1Pair),30AWG(1Pair+MAE)X2
AL FOIL+BRAID
INSULATOR MATERIAL:S/R PVC & HD-PE&FM-PE;
OUTSIDE JACKET MATERIAL:PVC;COLOR:BLUE
- 3.ELECTRIC TESTING:
1. 100% OPEN &SHORT TESTING
2. INSULATION RESISTANCE: ≥20MΩ
3. CONDUCTOR RESISTANCE: ≤ 5Ω
4. VOLTAGE: 500V DC/0.1S

ElectronicLinks
international inc

THIS DOCUMENT SHALL NOT BE REPRODUCED, NOR SHALL THE INFORMATION CONTAINED HEREIN BE USED OR DISCLOSED TO OTHERS EXCEPT AS AUTHORIZED IN WRITING BY ELECTRONIC LINKS INTERNATIONAL, INC.

UNLESS OTHERWISE NOTED:
DIMENSIONS IN MM

MATERIAL: AS NOTED

FINISH: AS NOTED

LINEAR
X.X = ±0.1
X.XX = ±0.05
X.XXX = ±0.025
X.XXXX = ±0.0125

ANGLES ± 0.2°

EDGE/
CORNER
BREAKS

OUTSIDE MAX. 0.5

INSIDE MAX. 0.15

SIZE C

REV LEVEL A

PART N

A05886


SCALE NONE

SHEET 1 of 1

USB 3.0 Cable Assembly
STD A PLUG STRAIGHT To Micro
USB B PLUG

REV	ECN	DESCRIPTION	DATE	DRAWN	APPROVED
1		Initial Release	03-22-13	jld	FLiburdi

CUSTOMER COPY



CONNECTOR PIN OUT




Table:

ITEM	DESCRIPTION	MATERIAL	P/N
D	STD A PLUG CONNECTOR	SPEC.	USB-9MASSXXX
C	USB3.0 CABLE	SEE NOTES 2	-----
B	OVERMOLD	60P PVC/BLUE 301U	-----
A	STD A PLUG CONNECTOR	SPEC.	USB-9MASSXXX

NOTES:


- 1.SPECIFICATIONS:
- VOLTAGE: 30 VAC(RMS)
- CURRENT: 1AMP MAX./CONTACT
- TERMINATION RESISTANCE: 30MILLIOHMS MAX.
- INSULATION RESISTANCE: 1000MEGOHMS MIN.
- DIELEC.WITHSTANDING VOLTAGE:750VAC
- CAPACITANCE: 2pF MAX.
- IMPEDANCE: 90 ±7 OHMS
- TEMP.RANGE: -40°C TO 60°C STORAGE
- HUMIDITY: 90 TO 95%RH
- THERMAL SHOCK: -55°C TO +85°C
- 2.CABLE SPEC.:
- UL20276,24AWG(2C),28AWG(1Pair),30AWG(1Pair+MAE)X2
- AL FOIL+BRAID
- INSULATOR MATERIAL:S/R PVC & HD-PE&FM-PE;
- OUTSIDE JACKET MATERIAL:PVC;COLOR:BLUE
- 3.ELECTRIC TESTING:
1. 100% OPEN &SHORT TESTING
2. INSULATION RESISTANCE: ≥20MΩ
3. CONDUCTOR RESISTANCE: ≤ 5Ω
4. VOLTAGE: 500V DC/0.1S

ElectronicLinks international inc THIS DOCUMENT SHALL NOT BE REPRODUCED, NOR SHALL THE INFORMATION CONTAINED HEREIN BE USED OR DISCLOSED TO OTHERS EXCEPT AS AUTHORIZED IN WRITING BY ELECTRONIC LINKS INTERNATIONAL, INC.			UNLESS OTHERWISE NOTED: DIMENSIONS IN MM			USB 3.0 Cable Assembly STD A PLUG STRAIGHT To STD A PLUG STRAIGHT					
			MATERIAL: AS NOTED								
			FINISH: AS NOTED								
			LINEAR								
			X.X = ±0.1 X.XX = ±0.05 X.XXX = ±0.025 X.XXXX = ±0.0125								
DESIGNED BY: SDR 02JUN05			ANGLES ± 0.2°			SIZE C		REV LEVEL A		PART N A05884	
CHECKED BY: XXX DD/MM/YY			EDGE/ CORNER BREAKS			OUTSIDE MAX. 0.5					
APPROVED BY: XXX DD/MM/YY			INSIDE MAX. 0.15			SCALE NONE				SHEET 1 of 1	

REV.	DATE	DESCRIPTION	BY
1.0	Jun/03/13'	D2852	Eve

DATE :	Jun/03/13'
P/N :	See the table
Dwg No:	A07214
CUST. P/N :	USB3C-AS/1-BS/1
CUSTOMER :	
DESCRIPTION	USB3C-AS/1-BS/1
APPROVE:	

CONFIGURATION



SPECIFICATION OF MATERIAL

1. END A

CONT. PLATING	Gold 15u"	MOLD No.	CMS-USB48	SHIELD'G	-
CONNECTOR TYPE	USB-9MASS15NBU			T. SCREW	Jack Screw M2 Size :4.5x39.00x7.00


2. END B

CONT. PLATING	Gold 15u"	MOLD No.	CMS-USB49	SHIELD'G	-
CONNECTOR TYPE	USB-9MBSS15NB			T. SCREW	Jack Screw M2 Size :4.5x39.00x7.00

3. WIRES

WIRE GAUGE	28Awg&28Awg&24Awg	LENGTH	L1	SHIELD'G	AB
CONDUCTORS	(1TP+MAE)x2+(1TP+AL)+2C	COLOR	Blue (301U)	UL/CSA	UL2725 (USB3.0)
JACKET MAT'L	PVC	INS. MAT'L	FM-SKIN-PE&FM-PE&SR-PVC	WIRE O.D.	5.5mm

4. CONNECTOR PIN OUT



5. SPECIAL REQUIREMENTS

- 5.1 Product requirement for Green environment protection:RoHS.
- 5.2 Overmold PVC is 45P Blue (Pantone No.:301U)(RoHS).
- 5.3 P/N :

P/N	LINE LENGTH	Cut length
B0106478	L=1000±30mm	L1=1000+20-0mm
B0106479	L=2000±30mm	L1=2000+20-0mm
B0106480	L=3000±50mm	L1=3000+30-0mm

* Standard Product